



Mole-Richardson Co.

TYPE 2461

**10,000 WATT
SKYLITE**



5

13

FEATURES


Provides a soft and even fill-light for lighting backings or extremely large cyc's in Television, Motion Pictures, and Still Photography. Diffuser Holder and Diffuser Frame are available for using diffusion materials for a softer fill-light. Equipped with Safety Screen.



Mole-Richardson Co.

TYPE 2461

10,000 WATT SKYLITE



GLOBE TABLE

Base, mogul bipost. Burn within 45° of vertical base-down. T-17, T-20, T-64 and G-64 bulb; 9" L.C.L.

Watts	Ordering Code	Color Temp.*K	Finish	Volts	Life Hours	Amps
10,000	DTY	3200	Clear	120	500	83.3
10,000	CP83	3200	Clear	230	500	41.6

Globes are not included in price of lamp.
See price list for complete details.

SPECIFICATIONS

HEAD: Type 2461, 10,000 watts.
RATING: 120/240 volts, A.C. or D.C., 100 amps max.—10,000 watts max.
SOCKETS: Mogul Bipost. Spring loaded contacts.
CABLE: 3 ft. Type SO, 3 conductor #4 AWG with MC258G 3 pin plug.
CONSTRUCTION: Steel reflector with cast aluminum socket housing.
YOKE: Tubular steel and brass castings with removable 1 1/8" dia. steel yoke pin.
REFLECTOR: Steel with white reflecting surface.
SIZE: 52" diameter by 23 1/4" deep reflector with skirt.
FINISH: Maroon Powder Coat Enamel.
HEAD WEIGHT: 73 lbs with Diffuser Holder
DIFFUSER HOLDER: Accessory Type 24637 with Type 34717 Safety Screen
 Required for mounting all light control accessories.

ACCESSORIES

- 24637 Diffuser Holder with Type 34717 Safety Screen
Required for mounting all light control accessories.
- 34724 Diffuser Frame (4' x 4')
- 19210 10kw to 5kw Socket Adapter
- 5001301 100 Amp Extension Cable—25 ft.
- 5001762 100 Amp Master Switch (120V)
- 42596 Trapeze
- 17032A Floor Spider (T-Bone)
- 500350 Heavy Duty C-Clamp and Adapter
For lamps having 1 1/8" dia. yoke pin.
- 500353 Heavy Duty C-Clamp and Adapter
Replaces radius end yoke pin.
- 500403 Adjustable Hanger Group
- 500424 Telescoping Hanger Group
Refer to Hanger Section.
- 500429 Stirrup Hanger Adapter



Type 24637
Diffuser Holder with
Type 34717 Safety Screen



Type 34724
Diffuser Frame



Type 5001301
25 FT. 100 Amp Extension Cable



Type 42596
Trapeze



Type 500350 Heavy Duty
Ball Bearing C-Clamp and
Adapter Assembly

PERFORMANCE DATA

Using DTY, 10,000 watt, 120 volt, 3200°K quartz globe.

Distance Feet	With Diffuser Holder	
	Light Intensity F.C.	Beam Diameter* Feet
5	3,780.0	15.4
10	945.0	30.8
15	420.0	46.2
20	236.3	61.6
25	151.2	77.0
30	105.0	92.1
35	77.1	107.5
40	59.1	122.9
45	46.7	138.2

*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.

