



Mole-Richardson Co.

TYPE 2591

2,000 WATT MOLEQUARTZ® 2K BABY "ZIP®" SOFTLITE



FEATURES

Designed to fill the need for a small compact Softlight with high performance for locations and small sets where space is at a minimum. All the light comes indirect and unobstructed from diffuse surfaces. For use with two 1,000 watt 3200°K quartz globes. Two switches control light intensity. Equipped with safety screen.



TYPE 2591 MOLEQUARTZ® 2K BABY "ZIP®" SOFTLIGHT MOUNTED ON TYPE 40651A BABY SIZE STANDARD STAND



Mole-Richardson Co.

TYPE 2591

2,000 WATT MOLEQUARTZ® 2K BABY "ZIP"® SOFTLITE



SPECIFICATIONS

HEAD: Type 2591, 2,000 watts.
RATING: 120/240 volts, A.C. or D.C., 16.7 amps max.—2,000 watts max.
SOCKETS: Compressible single contract. (Two per globe).
CABLE: Attached 25 feet, Type SO, 3 conductor #14 AWG. (Specify type of plug when ordering).
SWITCHES: 2 Toggle switches mounted on lamp. (One per globe).
CONSTRUCTION: Solid and perforated sheet steel.
YOKE: Cast aluminum. Fits any standard 5/8" dia. stand spud or 5/8" hanger spud.
REFLECTING SURFACES: Globe trough: Molebrite® specular aluminum. Reflecting hood: Special diffusing coating
FINISH: Maroon Powder Coat Enamel.
SIZE: 8" x 17 1/2" aperture.
HEAD WEIGHT: 13 3/4 lbs. (w/cable).

ACCESSORIES


- 2595 Egg Crate
- 25930 Diffuser Frame (18 1/4" x 8 1/4")
- 25979S Single Moledura Scrim (18 1/4" x 8 1/4")
- 25979D Double Moledura Scrim (18 1/4" x 8 1/4")
- 25950 2-Leaf Light Shield
- 25912 Snoot (6")
- 25913 Snoot (18")
- 25995 Safety Screen Kit (Can be retrofitted to previous models/Included with new units)
- 500848 C-Clamp and Adapter
- 259101 Replacement Reflector (Inserts for Hood Reflector/No Repainting Required)
- 40651A Baby Size Standard Stand (See Stand Section for more information & options)

GLOBE TABLE

Base, recessed single contact. Burn horizontal ± 4°. T-3 bulb; 4 11/16" M.O.L.

Watts	Ordering Code	Color Temp.°K	Finish	Volts	Life Hours	Amps
1000	FCM	3200	Clear	120	400	8.3
1000	FHM	3200	Frost	120	400	8.3
800	EME	3200	Clear	240	250	3.3
800	EMF	3200	Frost	240	250	3.3
750	EJG	3200	Clear	120	400	6.3
750	EMD	3200	Frost	120	400	6.3
500	FDN	3200	Clear	120	400	4.2
500	FDN	3200	Frost	120	400	4.2
500	FCL	3000	Clear	120	2000	4.2
500	FCZ	3000	Frost	120	2000	4.2
300	EHM	2950	Clear	120	2000	2.5
300	EHZ	2950	Frost	120	2000	2.5


Globes not included in price of lamp.
 See price list for complete details.



Type 2595 Egg Crate



Type 25930 Diffuser Frame



Type 25979D Double Moledura Scrim



Type 500764 C-Clamp and Adapter



Type 259101 Replacement Reflector

PERFORMANCE DATA

Using FCM-Q1000T3/4CL, 1,000 Watt, 120 volt, 3200° K quartz globe.

Distance Feet	Light Intensity F.C.	Lighted Area Dimension*—Feet	
		Width	Height
4	200	5.3	5.3
6	90	11.6	10.3
8	50	17.4	15.5
10	30	23.2	20.7
12	20	29.0	25.8

*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.

