



Mole-Richardson Co.

TYPE 2911

650 WATT MOLEQUARTZ® ONE-LIGHT NOOKLITE



FEATURES

Designed primarily for those hard-to-get-at locations where a flat even fill light is needed. Equipped with mounting brackets for attaching to wall, ceiling, post or any flat surface. For use in cars, buses or airplanes for interior lighting. Can be used for copyboard lighting. Compact and with high intensity for TV news coverage. Equipped with safety screen.





Mole-Richardson Co.

TYPE 2911

650 WATT

MOLEQUARTZ®

ONE-LIGHT NOOKLITE



GLOBE TABLE

Base, recessed single contact. Burn any position. T-4 bulb; 3 1/8" M.O.L.

Watts	Ordering Code	Temp.*K	Color	Finish	Volts	Life Hours	Amps
800	DXX	3200	Clear	230/240	75	3.53.3	
650	FAD	3200	Clear	120	100	5.4	
650	FBX	3200	Frost	120	100	5.4	
650	DWY	3400	Clear	120	25	5.4	
420	FFM	3200	Clear	120	75	3.5	
400	FDA	3200	Clear	120	250	3.3	
400	EHR	3000	Clear	120	2000	3.3	
300	EHP	2900	Clear	120	2500	2.5	

Globes not included in price of lamp.
See price list for complete details.

SPECIFICATIONS

HEAD: Type 2911, 650 watts.

RATING: 120/240 volts, A.C. or D.C., 5.4 amps max.—650 watts max.

SOCKETS: Compressible single contact. (Two per globe).

CABLE: Attached 25 ft., Type SO, 3 conductor #18 AWG. (Specify type of plug when ordering).

SWITCH: Thru-cord type in cable.

CONSTRUCTION: Solid and perforated sheet steel.

REFLECTOR: Aluminum, special Molebrite® Alzak surface.

FINISH: Maroon Powder Coat Enamel


SIZE: 8 1/8" x 3 9/16" x 1 11/16".

HEAD WEIGHT: 3 lbs. (w/cable).

YOKE: Accessory Type 29120. Formed steel with integral tube and clamp knob. Fits any standard 5/8" dia. stand spud or 5/8" hanger spud.

ACCESSORIES

- 29120 Yoke
- 29145 Accessory Holder
- 29132 2-Leaf Light Shield
- 29134 4-Leaf Light Shield
- 29172 2-Leaf Light Shield (Long Leaf)
- 29174 4-Leaf Light Shield (Long Leaf)
- 29194 Accessory Holder (For 1K Nooklite Accessories)
- 2922 2-Leaf Light Shield (For use with 29194 Accessory Holder)
- 2924 4-Leaf Light Shield (For use with 29194 Accessory Holder)
- 2928S Single Moledura Scrim (7 1/16" x 5 7/16") (For use with 29194 Accessory Holder)
- 2928D Double Moledura Scrim (7 1/16" x 5 7/16") (For use with 29194 Accessory Holder)
- 29113 Handle
- 2911B Blue Molocolor Daylight Conversion Filter
- 29175 Dichroic Daylight Conversion Filter
- 2355 Base Plate
- 500848 C-Clamp with 5/8" Spud



Type 29120
Yoke



Type 29174
4-Way Light Shield



Type 29194
Accessory Holder



Type 2924
4-Way Light Shield



Type 2928S
Single Moledura Scrim

PERFORMANCE DATA

Using FAD 650 Watt, 120 volt, 3200° K quartz globe.

Distance Feet	Light Intensity F.C.	Lighted Area Dimension*—Feet	
		Width	Height
4	340	7	6
8	85	14	12
12	40	21	18
16	20	28	24

*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.

