



# Mole-Richardson Co.

**TYPE 2921**

**1,000 WATT  
MOLEQUARTZ®  
1K NOOKLITE**



## FEATURES

Primarily designed to fit into wall corners, small nooks or on ceilings, the unit has literally dozens of other applications where lighting in tight or confined areas presents a problem. Equipped with safety screen.



TYPE 2921 MOLEQUARTZ® NOOKLITE  
MOUNTED ON TYPE 2541 COMPACT  
LITEWATE BABY SIZE STAND



# Mole-Richardson Co.

**TYPE 2921**   
**1,000 WATT**  
**MOLEQUARTZ®**  
**1K NOOKLITE**



**SPECIFICATIONS**

**HEAD:** Type 2921, 1,000 watts.  
**RATING:** 120/240 volts, A.C. or D.C., 8.3 amps max.—1,000 watts max.  
**SOCKETS:** Compressible single contact. (Two per globe).  
**CABLE:** Attached 25 ft., Type SO, 3 conductor #16 AWG. (Specify type of plug when ordering).  
**SWITCH:** Thru-cord type in cable.  
**CONSTRUCTION:** Solid and perforated sheet steel.  
**YOKE:** Cast aluminum. Fits any standard 5/8" dia. stand spud or 5/8" hanger spud.  
**REFLECTOR:** Aluminum, special Molebrite® Alzak surface.  
**FINISH:** Maroon Powder Coat Enamel  
**SIZE:** 9" x 4 5/8" x 1 7/8".  
**HEAD WEIGHT:** 4 1/2 lbs. (w/cable).

**ACCESSORIES**

- 2922 2-Leaf Light Shield
- 2924 4-Leaf Light Shield
- 2925 Accessory Holder
- 2928S Single Moledura Scrim (5 7/16" x 7 1/16")  
Accessory Holder needed for mounting.
- 2928D Double Moledura Scrim (5 7/16" x 7 1/16")  
Accessory Holder needed for mounting.
- 2926 Blue Molocolor Daylight Conversion Filter  
Accessory Holder needed for mounting.
- 2927 Dichroic Daylight Conversion Filter  
Accessory Holder needed for mounting.
- G136 Scrim Bag
- 500848 C-Clamp and Adapter
- 2541 Compact Litewate Baby Size Stand  
(See Stand Section for more information & options)

**GLOBE TABLE**


Base , recessed single contact. Burn horizontal ±4°. T-3 bulb; 4 1 1/16" M.O.L.

Watts	Ordering Code	Color Temp.*K	Finish	Volts	Life Hours	Amps
1000	FCM	3200	Clear	120	500	8.3
1000	FHM	3200	Frost	120	500	8.3
800	EME	3200	Clear	240	250	3.3
800	EMF	3200	Frost	240	250	3.3
750	EJG	3200	Clear	120	400	6.3
750	EMD	3200	Frost	120	400	6.3
500	FDG	3200	Clear	120	400	4.2
500	FDN	3200	Frost	120	400	4.2
500	FCL	3000	Clear	120	2000	4.2
500	FCZ	3000	Frost	120	2000	4.2
300	EHM	2950	Clear	120	2000	2.5
300	EHZ	2950	Frost	120	2000	2.5

Globes not included in price of lamp.  
 See price list for complete details.



Type 2924  
4-Way Light Shield



Type 2926 Blue Molocolor  
Daylight Conversion Filter



Type 2928S  
Single Moledura Scrim



Type 2925  
Accessory Holder



Type G136  
Scrim Bag

**PERFORMANCE DATA**

Using FCM-Q1000T3/4CL, 1,000 Watt, 120 volt, 3200° K quartz globe.

Distance Feet	Light Intensity F.C.	Lighted Area Dimension*—Feet	
		Width	Height
4	935	5.2	2.9
8	245	10.4	5.8
12	110	15.6	8.7
16	60	20.9	11.6
20	40	26.1	14.6
24	27	31.3	17.5
28	20	36.5	20.4

\*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.

