



Mole-Richardson Co.

TYPE 3041

1,000 WATT MOLEQUARTZ® BABY MOLEPOLE SOFTLITE



TYPE 3041 MOLEQUARTZ®
1K BABY MOLEPOLE "ZIP" SOFTLITE
MOUNTED ON TYPE 1201 C-CLAMP

FEATURES

The 1K Baby Molepole Softlite is designed for pole operation, pan and tilt with fixture hanging on pipe. This Softlite will fit in tight locations and small sets where space is limited. Now adjustable from the floor with our Molepole. Equipped with safety screen.



Mole-Richardson Co.

TYPE 3041 **CE** 1,000 WATT BABY MOLEPOLE SOFTLITE



GLOBE TABLE

Base—recessed single contact.
Burn horizontal $\pm 4^\circ$. T-3 bulb. $4\frac{11}{16}$ "
M.O.L.

Watts	Ordering Code	Color Temp.°K	Finish	Volts	Life Hours	Amps
1000	FCM	3200	Clear	120	400	8.3
1000	FHM	3200	Frost	120	400	8.3
800	EME	3200	Clear	240	250	3.3
800	EMF	3200	Frost	240	250	3.3
750	EJG	3200	Clear	120	400	6.3
750	EMD	3200	Frost	120	400	6.3
500	FDG	3200	Clear	120	400	4.2
500	FDN	3200	Frost	120	400	4.2
500	FCL	3000	Clear	120	2000	4.2
500	FCZ	3000	Frost	120	2000	4.2
300	EHM	2950	Clear	120	2000	2.5
300	EHZ	2950	Frost	120	2000	2.5

Globes are not included in price of lamp.
See price list for complete details.

SPECIFICATIONS

HEAD: Type 3041, 1,000 watts.
RATING: 120/240 volts, A.C. or D.C.,
8.3 amps max., 1,000 watts max.
SOCKETS: Compressible single contact. (2 per globe.)
CABLE: Attached 3 ft., Type SO, 3-conductor #16 AWG.
(Specify type of plug when ordering.)
SWITCH: Not applicable.
CONSTRUCTION: Solid and perforated sheet steel.
YOKE: Tubular aluminum and aluminum castings, into which the horizontal and vertical movement systems are integrated. $\frac{13}{16}$ " dia. spud attachment Accessory Type 1201 C-clamp.
REFLECTING SURFACES: Globe Trough: Molebrite® specular aluminum. Reflecting Hood: Special diffusing coating.
FINISH: Maroon Powder Coat Enamel.
SIZE: 8" x 8" aperture.
C-CLAMP TO CENTER: $15\frac{1}{4}$ ".
HEAD WEIGHT: 7 lbs. (w/cable).

ACCESSORIES

- 1201 C-Clamp
Accessory 1201 C-Clamp needed to hang 3041
- 25827 Egg Crate
- 25830 Diffuser Frame (8" x 8")
- 25876S Single Moledura Scrim (8" x 8")
- 25876D Double Moledura Scrim (8" x 8")
- 25850 2-Leaf Light Shield
- 25864 Snoot (6")
- 25844 Snoot (12")
- 81861 Safety Cable
- 42080 Molepole (3 ft.)
- 42081 Molepole (6 ft.)
- 42082 Molepole (12 ft.)
- 25892 Replacement Reflector
(Inserts for Hood Reflector/No Repainting Required)



Type 1201
C-Clamp



Type 25827
Egg Crate



Type 25864
Molesnoot 6"



Type 81861
Safety Cable



Type 42080
3' Molepole

PERFORMANCE DATA

Using EJG-Q750T3/4CL, 1,000 Watt, 120 volt, 3200° K quartz globe.

Distance Feet	Light Intensity F.C.	Beam Diameter* Feet
4	200	5.6
6	90	8.4
8	50	11.2
10	30	14.0
12	20	16.8

*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.

