



BALLASTS

TYPE 82833

200W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—90 to 230 Volts AC., 50 or 60 Hz 5A max.
CONTROL SWITCHES: ON and OFF rocker switch mounted on Ballast control panel. Maybe reignited when hot.
CIRCUIT PROTECTION: Fuse, 5 Amp.
CABLE: 5 ft., Attached to Ballast.
CONSTRUCTION: Solid and slotted sheet aluminum.
FINISH: Anodized Aluminum.
SIZE: 10" x 6¹/₄" x 3".
BALLAST WEIGHT: 5 lbs.



TYPE 82850

200W ELECTRONIC DC SQUAREWAVE BALLAST

RATING: Input—24 to 32 Volts DC., 11A max.
CONTROL SWITCHES: Inline ON and OFF rocker switch mounted on power cord.
CIRCUIT PROTECTION: Internal 15 Amp Fuse.
CABLE: 4 ft., Attached to Ballast.
CONSTRUCTION: Solid and slotted sheet aluminum.
FINISH: Anodized Aluminum.
SIZE: 7" x 4¹/₄" x 3".
BALLAST WEIGHT: 3 lbs.



TYPE 82926

400W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—90 to 260 Volts AC., 50 or 60 Hz 7.5A max.
CONTROL SWITCHES: ON and OFF rocker switch mounted on Ballast control panel. Maybe reignited when hot.
CIRCUIT PROTECTION: Fuse, 10 Amp.
CABLE: 5 ft., Attached to Ballast.
CONSTRUCTION: Solid and slotted sheet aluminum.
FINISH: Anodized Aluminum/Powder Coated Enamel.
SIZE: 11" x 7¹/₂" x 6¹/₄".
BALLAST WEIGHT: 8 lbs.



TYPE 64970

575W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—90 to 260 Volts AC., 50 or 60 Hz 8.2A max.
CONTROL SWITCHES: ON and OFF rocker switch mounted on Ballast control panel. Maybe reignited when hot.
CIRCUIT PROTECTION: Fuse, 10 Amp.
CABLE: 5 ft., Attached to Ballast.
CONSTRUCTION: Solid and slotted sheet aluminum.
FINISH: Anodized Aluminum/Powder Coated Enamel.
SIZE: 8.25" x 4.25" x 7.5".
BALLAST WEIGHT: 4 lbs.



Mole-Richardson Co.

BALLASTS



TYPE 68220

800W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—90 to 220 Volts AC., 50 or 60 Hz 9.1A max.

CONTROL SWITCHES: ON and OFF push button mounted on Ballast control panel. Maybe reignited when hot.

CIRCUIT PROTECTION: Fuse, 15 Amp.

CABLE: 5 ft., Attached to Ballast.

CONSTRUCTION: Solid and slotted sheet aluminum.

FINISH: Anodized Aluminum.

SIZE: 9" x 8½" x 5".

BALLAST WEIGHT: 6 lbs.



TYPE 63765

575W/1,200W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—90 to 230 Volts AC., 50 or 60 Hz 15A max.

CONTROL SWITCHES: ON and OFF push button mounted on Ballast control panel. Maybe reignited when hot.

CIRCUIT PROTECTION: Double pole circuit breaker and red indicator light.

CABLE: 6 ft., Attached to Ballast.

CONSTRUCTION: Solid sheet aluminum with aluminum fins

FINISH: Anodized Aluminum.

SIZE: 11½" x 9" x 7".

BALLAST WEIGHT: 17 lbs.



TYPE 638185

2,500W/4,000W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—95 to 260 Volts AC., 50 or 60 Hz 33.6A max.

CONTROL SWITCHES: ON and OFF push button mounted on Ballast control panel.

CIRCUIT PROTECTION: Double pole circuit breaker and red indicator light.

CABLE: X ft., Attached to Ballast.

CONSTRUCTION: Solid and slotted sheet aluminum.

FINISH: Anodized Aluminum.

SIZE: 15" x 10½" x 9½".

BALLAST WEIGHT: 31 lbs.

TYPE 66569

4,000W/6,000W ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—195 to 260 Volts AC., 50 or 60 Hz 65A max.

CONTROL SWITCHES: ON and OFF push button mounted on Ballast control panel.

CIRCUIT PROTECTION: Circuit breaker.

CABLE: Type 665XX 5 ft., Detachable with Veam type connector with customer specified connector.

CONSTRUCTION: Solid and perforated sheet aluminum with cart

FINISH: Anodized Aluminum.

SIZE: 22" x 20½" x 27". (48.5" high with handle raised)

BALLAST WEIGHT: 95 lbs.



BALLASTS

TYPE 66065

12,000W/18,000W

ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—208 to 240 Volts AC., 50 or 60 Hz 80A max.

CONTROL SWITCHES: ON and OFF push button mounted on Ballast control panel.

CIRCUIT PROTECTION: Double pole circuit breaker and red indicator light.

CABLE: Type 66066 5 ft., Detachable with Veam type connector with customer specified connector.

CONSTRUCTION: Solid and perforated sheet aluminum with cart

FINISH: Anodized Aluminum.

SIZE: 30" x 20½" x 27". (48.5" high with handle raised)

BALLAST WEIGHT: 140 lbs.



3

18

TYPE 680229

12,000W/18,000W/24,000W

ELECTRONIC AC SQUAREWAVE BALLAST

RATING: Input—208 to 240 Volts AC., 50 or 60 Hz 80A max.

CONTROL SWITCHES: ON and OFF push button mounted on Ballast control panel.

CIRCUIT PROTECTION: Double pole circuit breaker and red indicator light.

CABLE: Type 66066 5 ft., Detachable with Veam type connector with customer specified connector.

CONSTRUCTION: Solid and perforated sheet aluminum with cart

FINISH: Anodized Aluminum.

SIZE: 30" x 20½" x 27". (48.5" high with handle raised)

BALLAST WEIGHT: 140 lbs.